

PLENUM LINEAR SLOT DIFFUSERS

RECTANGLE

PSD20

ORDERING INFORMATION

MODEL	NUMBER OF SLOTS	SPACING	INSULATION	PLENUM MOUNTING BRACKET	NUMBER OF INLETS	FINISHING	STANDARD INLET SIZES	STANDARD LENGTH SIZES
PSD20	1	34	--	--	--	--	--	--

<p>↑</p> <p>PSD20: Supply RPSD20: Return without Blade</p>	<p>↑</p> <p>1: One Slot 2: Two Slots 3: Three Slots 4: Four Slots</p>	<p>↑</p> <p>34: 3/4" 10: 1" 15: 1 1/2"</p>	<p>↑</p> <p>--: Standard I: Insulation</p>	<p>↑</p> <p>--: Standard B: Plenum Mounting Bracket</p>	<p>↑</p> <p>--: 1 inlet per 1 meter 1: 1 inlet 2: 2 inlets 3: 3 inlets 4: 4 inlets 5: 5 inlets 6: 6 inlets</p>	<p>↑</p> <p>--: Brut RAL 9010: Pure White Semi Matt RAL "num" : Other Ral color</p>	<p>↑</p> <p>6 8 10 12</p>	<p>↑</p> <p>20 24 40 48</p>
--	---	--	--	---	--	---	---------------------------------------	---

N.B: - The available lengths of 12" inlet size are 40" and 48"
 - Insulation is not applicable for model RPSD20
 - For more information, please check the submittal sheet
 - Plenum Linear Slot Diffusers with length that exceed 80" (200 cm) are manufactured as multiple section and field assembled by others. Also, drawings should be agreed on with our engineers

ROUND VOLUME CONTROL DAMPER

For Round Volume Control Damper, Please refer to "KAC" submittal sheet and order information. The damper will be shipped loose.

Standard Inlet Size	Dimensions		
	A mm	B mm	H mm
6": Oval	160	130	254
8": Oval	230	130	254
10": Oval	320	130	254
12": Oval	380	130	254

	W mm			
	Number of Slots			
	1	2	3	4
S = 3/4"	45	89	130	178
S = 1"	50	100	150	200
S = 1 1/2"	63	125	190	250

